

RUBINETTI A CORSOIO SLIDE VALVE

CARATTERISTICHE TECNICHE PRINCIPALI MAIN TECHNICAL FEATURES

HAUPTTECHNISCHE DATEN PRINCIPALES CARACTERISTIQUES TECHNIQUES

Corpo principale
Main body



Manicotto esterno
Outer sleeve

MATERIALI DI COSTRUZIONE CONSTRUCTION MATERIALS

HERSTELLUNGSMATERIAL MATERIEL DE FABRICATION

Ottone cromato (EN12164-CW614N) - Manicotto in alluminio anodizzato
Chrome brass(EN12164 - CW614N) - Outside sleeve in anodized aluminium
Messing verchromtes (EN12164-CW614N) Aussen-hülse aus aluminium schwarz
Laiton Chromé (EN12164 - CW614N) - Manchon en aluminium anodisé



-10°C (263 K)
+80°C (353K)



0÷16 BAR (0÷1 MPa)

TIPOLOGIE DI ATTACCO FILETTATO THREADED CONNETTOR TYPE

ARTEN VON GEWINDENSCHLUSS TYPE DE CONNEXION FILETEE



Cilindrico femmina
Female parallel

Zylindrisches, innengewinde
Cylindrique femelle

UNI-ISO 228/1

O-RING/GUARNIZIONI O-RING/RUBBER-GASKET

DICHTUNGEN JOINTS

Guarnizioni in gomma antiolio NBR, esenti silicone
Oil-proof rubber packings NBR, silicon free

Dichtungen NBR, Ölbeständig, silikonfrei
Joints en caoutchouc anti-huile NBR, libres de silicone

CODIFICA RUBINETTI A CORSOIO SLIVE COUPLING LINE CODING

BESTELLNUMMERSYSTEM HANDSCHIEBEVENTIL SLIVE COUPLING LINE CODING

Serie articolo - Series - Serie - Séries

RC_

008

Filetto - Thread - Gewinde - Filet